


SCOPIA XT Telepresence Platform

Immersive Telepresence Customized to Your Unique Requirements



Immersive Life-like Experience

Replicate the feeling of meeting in person. The SCOPIA XT Telepresence Platform incorporates state-of-the-art technology with support for full HD 1080p video, 48 kHz full band audio and 1080p 30fps PC data sharing for an immersive life-like experience.



Customizable and Flexible

The SCOPIA XT Telepresence Platform delivers an immersive telepresence experience tailored to the unique requirements of individual rooms and customer needs. Installed and configured by our worldwide network of expert partners, the Platform provides a cost-effective and flexible telepresence deployment approach with optimal quality in all conditions ensured through powerful calibration and setup tools.



Market Leading Interoperability

The SCOPIA XT Telepresence Platform combined with the SCOPIA Elite MCU delivers unmatched interoperability with telepresence systems from Cisco®/Tandberg®, Logitech®/LifeSize® and Polycom® as well as with any standards-based video conferencing system for full video, audio and H.239 data collaboration.



Intuitive Apple iPad Control

The learning curve for using the SCOPIA XT Telepresence Platform is virtually eliminated with the SCOPIA Control Multi-Touch™ application for the Apple iPad®. First time users can initiate calls, control their SCOPIA XT Telepresence systems and moderate meetings without any training or introduction.



Breakthrough Price Point

The SCOPIA XT Telepresence Platform enables the creation of an exceptional immersive experience at a breakthrough price point. The Telepresence Platform stands out amongst the competition delivering immersive collaboration capabilities for a fraction of what competitors charge.

Specifications

Platform Components

- 3 x Telepresence licenses for the 3 SCOPIA XT1200 video conferencing systems, unlocking the Telepresence feature
- Camera support for the 3 cameras
- Control program available for the Apple iPad¹
- Calibration program available for Windows® PC
- SCOPIA iVIEW Management server with internal gatekeeper software license
- SCOPIA Desktop server software license
- System Integrator's Deployment Guide

Mandatory Components (not included)

- 3 x SCOPIA XT1200 video conferencing systems

Components to be Provided by the Integrator

- Table and chairs, based on the design guidelines provided by RADVISION
- 3 displays (50" and above as recommended) and wall mounts
- Audio amplifier and speakers (unless using the ones included in the displays)
- An iPad with an adequate dock
- An optional projector or a fourth display for data collaboration
- A PC server for iVIEW and SCOPIA Desktop

Display Support

- 3 x HD video monitor display via HDMI codec interfaces 50", 55", 60", 65" suggested size; 65" recommended (video monitors must be identical - same model, manufacturer, size and resolution)
- HD data monitor display via HDMI main codec interface 42 – 50", up to 1920 x 1080

HD Cameras

- 3 x Sony® EVI HD7 cameras
- Resolution: 1920 x 1080
- Locked PTZ position set
- Color and brightness calibration
- Fixed focus
- Simple Windows PC camera calibration tool for precise setup

Video

Video Resolution & Format

- 1080p (1920 x 1080) per codec @ 2 Mbps or higher
- 720p (1280 x 720) per codec @ 768 kbps or higher
- 16 x 9 aspect ratio

Video Standards

- H.261, H.263, H.263+, H.264 and H.239 data

Video Inputs (3+1 Inputs)

- 3 x HDMI camera inputs (one per codec)
- 1 x DVI-I PC input DVI/XGA with cable adapter included (main codec)

Video Outputs (3+1 Outputs)

- 3 x HDMI output for HD video (one per codec)
- 1 X HDMI output for H.239 data content (main codec)

Audio

Audio Features

- 2 x Digital microphone array pods (cascading)
- Mute button
- Frequency response: 50 – 22,000 Hz
- All audio inputs and outputs are connected to the main codec

Audio Standards

- G.711, G.722, G.722.1C, G.719, AAC-LD

Audio Inputs

- 1 x SPDIF (RCA)
- 1 x Pod (RJ-11)
- 1 x 3.5 mm (1/8") line in jack

Audio Outputs

- 1 x HDMI
- 1 x SPDIF (RCA)
- 1 x 3.5 mm (1/8") line out jack

User Interface

- SCOPIA Control Apple iPad Multi-Touch™ application¹
- Camera calibration tool for Windows PC

Web Management

- Configuration, call features via Web are not available, diagnostics and management functions are accessible with: Internet Explorer™7.0+, Firefox 3.0®+, Safari 3.0®+

Network Requirements

- 6 – 12 Mbps (2 – 4 Mbps per codec)
- 3 x 10/100/1000 Base-T full-duplex interfaces (RJ-45)

Power Requirements

- 3 x 100 – 240 VAC, 50-60 Hz, 2.5 A max.

RADVISION Solution Requirements

- Point-to-point SCOPIA Telepresence: SCOPIA iVIEW Management with internal gatekeeper and SCOPIA Desktop
- Multi-party with standard HD and 3rd party Telepresence systems: SCOPIA iVIEW Management with internal gatekeeper, SCOPIA Desktop and SCOPIA Elite MCU with Telepresence Interoperability

¹ SCOPIA Control is unlocked by the Telepresence license. The software can be downloaded for free from the Apple App Store. iPad and iPad dock are not included.

For additional specification details please refer to the SCOPIA XT1200 datasheet.

About RADVISION

RADVISION (Nasdaq: RVSN) is the industry's leading provider of market-proven products and technologies for unified visual communications over IP and 3G networks. With its complete set of standards-based video communications solutions and developer toolkits for voice, video, data and wireless communications, RADVISION is driving the unified communications evolution by combining the power of video, voice, data and wireless – for high definition video conferencing systems, innovative converged mobile services, and highly scalable video-enabled desktop platforms on IP, 3G and emerging next-generation networks. For more information about RADVISION, visit www.radvision.com

USA/Americas
T +1 201 689 6300
F +1 201 689 6301
infoUSA@radvision.com

EMEA
T +44 20 3178 8685
F +44 20 3178 5717
infoUK@radvision.com

APAC
T +852 3472 4388
F +852 2801 4071
infoAPAC@radvision.com