



VidyoRoom™ HD-220

Step inside a conference room outfitted with the VidyoRoom HD-220 room system and be prepared to rethink what you know about videoconferencing. No more lost time in making complicated connections or waiting for IT support to start the conference! The VidyoRoom HD-220's intuitive user interface makes starting a conference as easy as pressing a button. Once that button is pressed, you and your conference participants will enjoy the natural, same-room feel and interactivity made possible by crisp, full HD, 60 FPS video with imperceptible latency. Delivered across two large HD screens, you'll be able to choose between active speaker and continuous presence layouts, independently of all other participants, via a click of a button. And just when you've gotten used to the fact that your Vidyo conference looks the same as your HD broadcast experience at home, your eyebrows will raise once more as you realize that all of this is taking place over converged IP networks and the Internet – no QoS required.

Welcome to the way telepresence was meant to be. The VidyoRoom HD-220 is affordable, simple to use, easy to configure and delivers amazing performance thanks to the VidyoRouter™ architecture. Like all VidyoRoom products, the VidyoRoom HD-220 interoperates seamlessly with VidyoDesktop™ clients, and with legacy H.264-based H.323 and SIP endpoints via the VidyoGateway™, making it possible to connect with anyone, anywhere using equipment they already have. And since a VidyoRoom does not consume a VidyoLine™ license for connectivity through the VidyoRouter, telepresence multipoint connectivity has never been more affordable.



VidyoRoom HD-220 raises the bar and changes the economics for room-based telepresence

VidyoRoom HD-220 Benefits:

- Easy to deploy and use
- Stunning HD quality without noticeable delay
- Works over general purpose IP networks
- Integrates seamlessly with VidyoDesktop and with legacy room systems via VidyoGateway
- Consumes no VidyoLine licenses – economical deployment and connectivity to other users

Features and Functions:

Video Performance

- PSTN-like glass to glass multi-point latency (not perceptible in call)
- Built-in network error concealment – optimal performance without QoS



User Interface

- Intuitive Graphical User Interface – consistent with the VidyoDesktop client - makes operating the VidyoRoom simple and straightforward
- Call initiation and entry into Private Meeting Room achieved with only one click
- IR remote and keyboard/mouse control options
- Multi-tap text entry when using the remote control keypad
- On-screen keyboard for convenient directory searches
- Dial pad for DTMF signaling (to support calls to legacy and voice endpoints)
- XML API for 3rd party control system integration (Crestron, AMX)
- Full and automatic integration with the VidyoPortal™ user's database. No need to maintain a local address book
- Self explanatory presence icons establish status of another user on the system
- Pop-up icon indicates that there is not an available video capture device





You and your conference participants will enjoy the natural, same-room feel and interactivity made possible by crisp, full HD, 60 FPS video with imperceptible latency.

VidyoRoom™ HD-220

- Call setup actions are context aware and based upon status of selected contacts
- Web-based configuration settings
- Auto-select or manually select number of participants viewed
- Local preview toggle

Data Sharing

- Participants can toggle between other users' shared windows (everyone can share concurrently)
- Laptop screen sharing through the optional VGA input device

Audio Controls

- Speakers volume adjustment and mute/unmute
- Microphone gain adjustment and mute/unmute

Camera Control

- Video privacy mode
- Local camera pan, tilt, zoom via remote control
- Advanced Far-End-Camera-Control during a conference

Security & Network

- Media Encryption: Optional 128bit AES
- Signal Encryption: Optional HTTPS

Administration & Maintenance

- Web-based administration for remote access and configuration
- Automatic software updates, downloadable from VidyoPortal
- Conference moderation via VidyoPortal



Delivered across two large HD screens, you'll be able to choose between active speaker and continuous presence layouts, independently of all other participants, via a click of a button.

VidyoRoom HD-220 Specifications:

APPLICATION SPECIFICATIONS

VIDEO STANDARDS

H.264 SVC
H.264 AVC, H.263+ via the VidyoGateway

VIDEO PERFORMANCE

Transmit resolution & frame rate at minimum bit rate

HD 1080p @ 30 fps @ 2Mbps min.
HD 720p @ 60fps @ 1Mbps min.
HD 720p @ 30 fps @ 768Kbps min.
540p @ 30 fps @ 512Kbps min.
360p @ 30 fps @ 512 Kbps min.

Receive resolution & frame rate at minimum bit rate

HD 1080p @ 30 fps @ 2Mbps min.
HD 720p @ 60 fps @ 1Mbps min.

Data sharing video resolution

Up to WXGA (fitted to screen resolution)

MAXIMUM DATA RATE

4 Mbps

AUDIO STANDARDS

SPEEX Wideband 32KHz (16KHz audio)
G.711 (A-, μ -Law), G.722, via VidyoGateway

LANGUAGE SUPPORT

English
French
German
Italian
Japanese
Korean
Portuguese
Simplified Chinese
Spanish

DISPLAY

Single-screen modes

Participants' video is spread evenly on the screen
Preferred larger voice-activated speaker
N+1 layout where N=up to 8 participants + 1 self view)

Dual-screen modes

Preferred larger voice-activated speaker on second screen with participants' video spread evenly on first
Participants' video is spread evenly on both screens
Data full screen on second screen

Aspect ratio

Full-screen, 16:9 aspect ratio



VidyoRoom HD-220 Specifications:

PHYSICAL SPECIFICATIONS

FORM FACTOR

Stand-alone Chassis,
(Freestanding or 19" Rack-mountable)

DIMENSIONS

Height 14.56" (370mm)
Width 3.44" (87.4mm)
Depth 12.59" (320mm)
Gross Weight 13.0 lbs (5.89kg)

PHYSICAL INTERFACES

Camera In

1 x HDMI

Camera Control

1 x RS-232 (through supplied Serial/USB dongle)

Video Out

2 x DisplayPort (through supplied DisplayPort
to DVI converter)

Audio In

1 x 3.5mm Stereo Jack, USB

Audio Out

1 x 3.5mm Stereo Jack, USB

USB-2

6 (2 front, 4 rear)

Network

1 x Gigabit Ethernet – Supports
10BASE-T, 100BASE-TX, and
1000BASE-T, RJ45 outputs

CONFIGURATION

Camera (Optional)

HD PTZ Camera, HDMI Interface

Microphones (Optional)

USB Echo Cancellation Speakerphone
w/ Noise Suppression

POWER SUPPLY

Auto-switching 300W AC to DC power
supply w/ PFC 100 - 240V, 50 - 60Hz,
4 - 2Amp

OPERATING ENVIRONMENT

Operating Temperature Range

10° to 35° C (50° to 95° F)

Non-Operating Temperature

-40° to 70° C (-40° to 158° F)

Humidity Range

8% - 90% (non-condensing)

Non-Operating Humidity Range

5% - 95% (non-condensing)

REGULATORY

EMI/EMC: EN55022, EN55024, FCC, VCCI,

Australian/New Zealand, MIC (Korea)

Safety: USA – TUV certified, Canada – TUV certified,

Europe/CE Mark EN 60950/IEC 60950-Compliant

China: CCC Certification

Environmental: RoHS compliant

Vidyo, Inc.

433 Hackensack Ave

Hackensack, NJ 07601

Phone: +1.201.289.8597

Toll-free: +1.866.998.4396

Fax: +1.201.490.5340

www.vidyo.com

© 2009, 2010 Vidyo, Inc. All rights reserved. VIDYO and other trademarks used herein are trademarks or registered trademarks of Vidyo, Inc. or their respective owners. All specifications subject to change without notice, system specifics may vary. This product is covered by one or more United States and/or foreign issued and/or pending patents.